


## TOP - 620/640M-144BI

144 CELL  
Mono N - Type Module620 - 640Wp  
Power Output Range1500VDC  
Maximum System Voltage22.90%  
Maximum Efficiency

## KEY SALIENT FEATURES



Industry leading lowest thermal co-efficient of power



Industry leading 15 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive power tolerance of 0~+3%



Fully automated production at all stages



Fully Reduced power loss by minimizing the effect of shadow shading ( 9 - 18 Busbar)



European Warranty &amp; After - Sales Service



## TAMESOL BUILDING A GREEN FUTURE S.L

TAMESOL is a global provider of high-efficiency PV panels with a 10GW annual production capacity and a 100% automated production line, innovating state-of-the-art products for over 15 years. Our panels have been installed in more than 50 countries, with over 20 million panels already connected to the grid.


Tel : +34 872 222 388

E - mail: [info@tamesol.com](mailto:info@tamesol.com) Website: [www.tamesol.com](http://www.tamesol.com)

**TAMESOL**  
Energia para vivir

## LINEAR PERFORMANCE WARRANTY

15 year Product Warranty / 30-Year Linear Power Warranty



*Since 2007, building a green future*

<b>22,90%</b> MAX MODULE EFFICIENCY	<b>0 - +3%</b> POWER TOLERANCE	<b>1,0%</b> FIRST YEAR POWER DEGRADATION	<b>0,40%</b> YEAR 2-30 POWER DEGRADATION	<b>N-TYPE CELL</b> Lower operating temperature
--	-----------------------------------	---	---	---


**ELECTRICAL CHARACTERISTICS**    STC: AM1.5 1.000W/m2    NOTC: AM1.5 800W/m2 20° 1 m/s    Test uncertainty for Pmax 0 - +3%

Module type	TOP - 620M-144BI		TOP - 625M-144BI		TOP - 630M-144BI		TOP - 635M-144BI		TOP - 640M-144BI	
	STC	NOTC	STC	NOTC	STC	NOTC	STC	NOTC	STC	NOTC
Maximum Power (Pmax/w)	620	466	625	470	630	474	635	478	640	481
Open Circuit Voltage (Voc/V)	52,07	49.47	52,27	49.66	52,47	49,85	52,67	50,04	52,87	50,23
Short Circuit Current (Isc/A)	15,11	11.95	15,16	12	15,21	12,04	15,26	12,09	15,31	12,28
Voltage at Maximum Power (Vmp/V)	43,51	41.34	43,71	41.53	43,90	41,71	44,10	41,90	44,29	42,09
Current at maximum Power (Imp/A)	14,25	11.27	14,30	11,32	14,35	11,36	14,40	11,41	14,45	11,43
Module Efficiency (%)	22,2%		22,4%		22,5%		22,7%		22,9%	

**MECHANICAL PARAMETERS**

Cell Orientation	single crystal N-Topcon 182x99.5mm (144 pieces)
Junction Box	IP68, three diodes
Output Cable	4.0mm <sup>2</sup> 300mm(+) / 300mm(-) or customized
Glass	2.0mm / 2.0mm
Frame	Anodized aluminum alloy frame
Weight	34,6 kg
Dimensión	2465*1134*35mm
Packaging	31 pcs*pallet / 496pcs*40HC

**PHYSICAL CHARACTERISTICS**



**OPERATING PARAMETERS**

Operational Temperature	-40°C - +85°C
Power Output Tolerance	(0, +3%)
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30 A
Nominal Operating Cell Temperature	45±2°C
Protection Glass	Class II
Fire Rating	Class C
Bifacial - Factor	80% ± 10%

**MECHANICAL LOADING**

Front Side Maximum Static Loading	5400 PA
Rear Side Maximum Static Loading	2400 PA

**TEMPERATURA RATINGS (STC)**

Temperature Coefficient of Isc	+0.046%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Pmax	-0.30%/°C

**PACKING MANNER**

Container	40ft(HQ)
Number of modules per container	496
Number of modules per pallet	31
Number of pallets per container	16

TAMESOL Authorized Solar Dealer

**Note:** The specifications are obtained under the Standard Test Conditions (STCs): 1000 W/m2 solar irradiance, 1.5 Air Mass, and cell temperature of 25°C. The NOCT is obtained under the Test Conditions: 800 W/m2, 20°C ambient temperature, 1m/s wind speed, AM 1.5 spectrum. Please contact [info@tamesol.com](mailto:info@tamesol.com) for technical support. The actual transactions will be subject to the contracts. This parameter is for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.