

PERC**MAX**

BIFACIAL

HIGH PERFORMANCE
BIFACIAL MONOCRYSTALLINE
P.E.R.C MODULE

132


TM - 485/505M-132BI

132 CELL
Mono PERC Module









485 - 505Wp
Power Output Range

1500VDC
Maximum System Voltage

21.50%
Maximum Efficiency



KEY SALIENT FEATURES

-  Industry leading lowest thermal co-efficient of power
-  Industry leading 15 years product warranty
-  Excellent low irradiance performance
-  Excellent PID resistance
-  Positive power tolerance of 0~+3%
-  Fully automated production at all stages
-  Fully Reduced power loss by minimizing the effect of shadow shading (9 - 18 Busbar)
-  European Warranty & After - Sales Service



TAMESOL BUILDING A GREEN FUTURE S.L


TAMESOL is a global provider of high-efficiency PV panels with a 10GW annual production capacity and a 100% automated production line, innovating state-of-the-art products for over 15 years. Our panels have been installed in more than 50 countries, with over 20 million panels already connected to the grid.

Tel : +34 872 222 388

E - mail: info@tamesol.com Website: www.tamesol.com

LINEAR PERFORMANCE WARRANTY

15 year Product Warranty / 30-Year Linear Power Warranty



TAMESOL 15
YEARS

Since 2007, building a green future

21,50%
MAX MODULE
EFFICIENCY

0 - +3%
POWER
TOLERANCE

2,0%
FIRST YEAR POWER
DEGRADATION

0,50%
YEAR 2-30
POWER DEGRADATION

PERC CELL
Lower operating temperature

ELECTRICAL CHARACTERISTICS


STC: AM1.5 1.000W/m2 NOTC: AM1.5 800W/m2 20° 1 m/s Test uncertainty for Pmax 0 - +3%

Module type	TM - 485M-132BI		TM - 490M-132BI		TM - 595M-132BI		TM - 500M-132BI		TM - 505M-132BI	
	STC	NOTC	STC	NOTC	STC	NOTC	STC	NOTC	STC	NOTC
Maximum Power (Pmax/w)	485	367	490	370	495	374	500	378	505	382
Open Circuit Voltage (Voc/V)	45.10	42.30	45,25	42.43	45.40	42.58	45,55	42.72	45.70	42.86
Short Circuit Current (Isc/A)	13,67	11.09	13,74	11.13	13.82	11.20	13,90	11.27	13,97	11.34
Voltage at Maximum Power (Vmp/V)	37.97	35.67	38,08	35.76	38.23	35.84	38.38	35.93	38.53	36.02
Current at maximum Power (Imp/A)	12,79	10.28	12,87	10.36	12.95	10,44	13.03	10.52	13,11	10.60
Module Efficiency (%)	20,60%		20,90%		21,10%		21,30%		21,50%	

MECHANICAL PARAMETERS

Cell Orientation	single crystal PERC 182 x91mm (132 pieces)
Junction Box	IP68, three diodes
Output Cable	4.0mm² 300mm / 1100mm
Glass	3.2mm tempered coated glass, low iron
Frame	Anodized aluminum alloy frame
Weight	25.5 kg
Dimensión	2094*1134*35mm
Packaging	31 pcs*pallet/ 792 pcs*40HQ

PHYSICAL CHARACTERISTICS



OPERATING PARAMETERS

Operational Temperature	-40°C - +85°C
Power Output Tolerance	(0, +3%)
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	25 A
Nominal Operating Cell Temperature	45±2°C
Protection Glass	Class II
Fire Rating	Class C
Bifacial- Factor	70%±10%

MECHANICAL LOADING

Front Side Maximum Static Loading	5400 PA
Rear Side Maximum Static Loading	2400 PA

TEMPERATURA RATINGS (STC)

Temperature Coefficient of Isc	+0.05%/°C
Temperature Coefficient of Voc	-0.27%/°C
Temperature Coefficient of Pmax	-0.35%/°C

PACKING MANNER

Container	40ft(HQ)
Number of modules per container	792
Number of modules per pallet	31
Number of pallets per container	26

TAMESOL Authorized Solar Dealer

Note: The specifications are obtained under the Standard Test Conditions (STCs): 1000 W/m2 solar irradiance, 1.5 Air Mass, and cell temperature of 25°C. The NOCT is obtained under the Test Conditions: 800 W/m2, 20°C ambient temperature, 1m/s wind speed, AM 1.5 spectrum. Please contact info@tamesol.com for technical support. The actual transactions will be subject to the contracts. This parameter is for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.